

UTILITY PATENT APPLICATION TRANSMITTAL
(Large Entity)

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Docket No.

F-10110

Total Pages in this Submission

TO THE ASSISTANT COMMISSIONER FOR PATENTS

Box Patent Application

Washington, D.C. 20231

Transmitted herewith for filing under 35 U.S.C. 111(a) and 37 C.F.R. 1.53(b) is a new utility patent application for an invention entitled:

NETWORK SWITCHING SYSTEM WITH ASYNCHRONOUS AND ISOCHRONOUS INTERFACE

and invented by:

Akira KoyamaIf a **CONTINUATION APPLICATION**, check appropriate box and supply the requisite information:☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No.: _____

Which is a:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No.: _____

Which is a:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No.: _____

Enclosed are:

Application Elements

1. ☒ Filing fee as calculated and transmitted as described below
2. ☒ Specification having 25 pages and including the following:
 - a. ☒ Descriptive Title of the Invention
 - b. ☐ Cross References to Related Applications (if applicable)
 - c. ☐ Statement Regarding Federally-sponsored Research/Development (if applicable)
 - d. ☐ Reference to Microfiche Appendix (if applicable)
 - e. ☒ Background of the Invention
 - f. ☒ Brief Summary of the Invention
 - g. ☒ Brief Description of the Drawings (if drawings filed)
 - h. ☒ Detailed Description
 - i. ☒ Claim(s) as Classified Below
 - j. ☒ Abstract of the Disclosure

UTILITY PATENT APPLICATION TRANSMITTAL (Large Entity)

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Docket No.

F-10110

Total Pages in this Submission

Application Elements (Continued)

3. ☒ Drawing(s) (when necessary as prescribed by 35 USC 113)

- a. ☒ Formal Number of Sheets 15 (Figs. 1-15)
- b. ☐ Informal Number of Sheets _____

4. ☒ Oath or Declaration

- a. ☒ Newly executed (original or copy) ☐ Unexecuted
- b. ☐ Copy from a prior application (37 CFR 1.63(d)) (for continuation/divisional application only)
- c. ☒ With Power of Attorney ☐ Without Power of Attorney
- d. ☐ DELETION OF INVENTOR(S)
Signed statement attached deleting inventor(s) named in the prior application,
see 37 C.F.R. 1.63(d)(2) and 1.33(b).

5. ☐ Incorporation By Reference (usable if Box 4b is checked)

The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby incorporated by reference therein.

6. ☐ Computer Program in Microfiche (Appendix)

7. ☐ Nucleotide and/or Amino Acid Sequence Submission (if applicable, all must be included)

- a. ☐ Paper Copy
- b. ☐ Computer Readable Copy (identical to computer copy)
- c. ☐ Statement Verifying Identical Paper and Computer Readable Copy

Accompanying Application Parts

8. ☒ Assignment Papers (cover sheet & document(s))

9. ☐ 37 CFR 3.73(B) Statement (when there is an assignee)

10. ☐ English Translation Document (if applicable)

11. ☒ Information Disclosure Statement/PTO-1449 ☒ Copies of IDS Citations

12. ☐ Preliminary Amendment

13. ☒ Acknowledgment postcard

14. ☐ Certificate of Mailing

☐ First Class ☐ Express Mail (Specify Label No.): _____

UTILITY PATENT APPLICATION TRANSMITTAL (Large Entity)

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Docket No.
F-10110

Total Pages in this Submission

Accompanying Application Parts (Continued)

15. ☒ Certified Copy of Priority Document(s) (if foreign priority is claimed)


16. ☐ Additional Enclosures (please identify below):

Fee Calculation and Transmittal

CLAIMS AS FILED

For	#Filed	#Allowed	#Extra	Rate	Fee
Total Claims	9	- 20 =	0	x \$18.00	\$0.00
Indep. Claims	6	- 3 =	3	x \$78.00	\$234.00
Multiple Dependent Claims (check if applicable) <input type="checkbox"/>					\$0.00
BASIC FEE					\$690.00
OTHER FEE (specify purpose) Assignment Recordation					\$40.00
TOTAL FILING FEE					\$964.00

- ☒ A check in the amount of \$964.00 to cover the filing fee is enclosed.
- ☒ The Commissioner is hereby authorized to charge and credit Deposit Account No. 50-0481 as described below. A duplicate copy of this sheet is enclosed.
- ☐ Charge the amount of as filing fee.
- ☒ Credit any overpayment.
- ☒ Charge any additional filing fees required under 37 C.F.R. 1.16 and 1.17.
- ☐ Charge the issue fee set in 37 C.F.R. 1.18 at the mailing of the Notice of Allowance, pursuant to 37 C.F.R. 1.311(b).


Signature

Dated: April 7, 2000

Sean M. McGinn, Esq.
Registration No. 34,386

CC:

Customer No. 21254

MCGINN & GIBB, P.C.
A PROFESSIONAL LIMITED LIABILITY COMPANY
PATENTS, TRADEMARKS, COPYRIGHTS, AND INTELLECTUAL PROPERTY LAW
1701 CLARENDON BOULEVARD, SUITE 100
ARLINGTON, VIRGINIA 22209
TELEPHONE (703) 294-6699
FACSIMILE (703) 294-6696

**APPLICATION
FOR
UNITED STATES
LETTERS PATENT**

APPLICANT: Akira Koyama

FOR: NETWORK SWITCHING SYSTEM WITH
ASYNCHRONOUS AND ISOCRONOUS
INTERFACE

DOCKET NO.: F-10110

NETWORK SWITCHING SYSTEM WITH ASYNCHRONOUS AND ISOCHRONOUS INTERFACE

BACKGROUND OF THE INVENTION

5

1. Technical Field of the Invention

The present invention relates to a switching method and equipment, wherein a serial bus is connected with extension nodes having asynchronous interfaces and isochronous
10 interfaces for switching signals between an outside line and extension lines and between the extension lines

2. Description of the Prior Art

Conventionally, switching devices for home use are simple, because they are provided merely with an analogue or digital
15 voice switch. Recently, however, information devices such as personal computers are introduced into the home, and digital broadcasting becomes popular. Therefore, there are growing needs for distributing image signal, data signal, voice and audio signal to an individual or to individuals
20 simultaneously.

Therefore, asynchronous transfer mode (ATM) and local area network (LAN) such as Ethernet are improved for distributing time series data such as audio-visual signal.

Further, IEEE 1394 (IEEE Std. 1394-1995 IEEE Standard
25 for a High Performance Serial Bus) is known by its real time and high speed performance, and plug-and-play capability. Therefore, IEEE 1394 can be used in a high speed network for multi-media signal into the home. IEEE 1394 applied to the home telephone is exemplified in Figure 15. As shown in

Figure 15, digital voice signal 601 loaded on IP packet (Internet Protocol packet) 603 is transmitted by asynchronous transfer of IEEE 1394 toward a person on the other end of the line. Voice signal 601 is recovered by assembling IP packet 603. Such a telephone system as explained above simply is called IP telephony defined by ITU-T H323.

However, ATM costs much, and Ethernet architecture can not guarantee the real time performance for a plurality of time series data streams.

On the other hand, home use switching equipment for voice, audio-video signals must be of low cost. In addition, it must have complete plug-and-play capability, when appliances are newly installed.

Actually, the IP telephony on IEEE 1394 as well as the IP telephony on the internet requires additional competent software, CPU, and hardware, such as codec for DSP (digital Signal Processing).

However, completely natural voice is hardly obtained in general by the IP telephony, because the time series data stream is processed by asynchronous system.

Further, in an advanced network, the plug-and-play capability is indispensable for automatic recognition of newly installed appliances.

Connection route is changed often or even stopped by a bus reset on IEEE 1394 for plug-and-play. However, the communication should not be interrupted by such a bus reset.

Furthermore, the communication quality should be maintained under fluctuations in data traffic.

Further, it is desirable to provide such an advanced network with API (Application Program Interface) compatible with various operating systems and protocols.

Further, each terminal can identify other terminals by
5 their ID numbers under the plug-and-play circumstance.

Furthermore, it is desirable to provide a telephone equipment with such functions as master-slave communication, slave-slave communication, master-slave transfer, and slave-slave transfer.

10

SUMMARY OF THE INVENTION

An object of the present invention is to provide a switching method and system, wherein the telephone switching in the
15 isochronous and asynchronous channels of IEEE 1394 is executed mainly by hardware.

A network switching system of the present invention exchanges stream data on a serial bus through a gateway between an outside line and an extension node, or between an
20 extension node and the other extension node, wherein the extension node comprises:

control/memory unit for storing physical identifiers and telephone numbers of the gateway node and extension nodes and for controlling the network;

25 an asynchronous interface, for selecting the extension node and controlling a switching timing, connected with the control/memory unit;

a rate conversion unit for converting data rate of the stream data in the network into that in the outside line, or

the other way around; and

an isochronous interface, for transmitting and receiving the stream data, connected with the rate conversion unit.

A gateway of the present invention comprises a first
5 switching unit for controlling extension nodes connected with a serial bus for isochronous transfer, and second switching unit for exchanging stream data between an outside line and the extension nodes, wherein:

the first switching unit comprises a bus manager
10 connected with an asynchronous interface and an isochronous interface; and

the second switching unit comprises a line manager connected with a codec and a control/memory unit,

wherein the line manager exchanges the stream data
15 between the outside line and the extension line, according to a request from the bus manager, and the bus manager manages a call-in to the extension node and a call-out from the extension node.

An information terminal of the present invention
20 comprises a telephone for transmitting and receiving telephone signal through a serial bus, a TV set for receiving TV signal through the serial bus, and a bus manager for controlling the serial bus, wherein the bus manager comprises two pairs of an asynchronous interface and an
25 isochronous interface for the telephone signal and the TV signal.

A gateway of the present invention comprises a telephone gateway and a TV gateway which are connected with a bus manager, wherein:

the telephone gateway transfers telephone signal from public switched telephone network to a serial bus, and the other way around;

the TV gateway receives TV signal from TV line, and
5 transfer the TV signal to the bus manager; and

the bus manager comprises two pairs of an asynchronous interface and an isochronous interface for transferring the telephone signal and the TV signal, respectively.

A call-in signal processing method of the present invention
10 for a network switching system using asynchronous and isochronous transfer, wherein stream data on a serial bus are exchanged through a gateway between an outside line and an extension node, or between an extension node and the other extension node, which comprises the steps of:

15 selecting at the gateway which of an automatic transfer by number display, a global call-in, or a manual call-in on the basis of setup data;

calling one or more extension nodes;

securing one or more isochronous channels on the basis of
20 responses from the extension nodes;

making the extension nodes start talking;

sending simultaneously call status of a station of which call status is changed, to all the extension node connected with the serial bus.

25 A call-out signal processing method of the present invention for a network switching system using asynchronous and isochronous transfer, wherein stream data on a serial bus are exchanged through a gateway between an outside line and an extension node, or between an extension

node and the other extension node, which comprises the steps of:

receiving at the gateway a call-out from the extension node ;

- 5 confirming at the gateway a call status of call object;
 securing an isochronous channel for transmission;
 sending the call status to all the extension nodes;
 securing an isochronous channel for reception;
 making the call object start talking, while sending, to the
- 10 extension node which has made the call-out, such a call
 status that indicates the object does not respond, when the
 object does not respond;
 releasing the isochronous channels for transmission and
 reception, when detecting an on-hook of the extension node
- 15 which has made the call-out; and
 sending the call status to all the extension nodes.

In the above-explained present invention, any special hardware such as ATM switch is not employed. The switching system of the present invention employs a high speed serial

20 bus such as IEEE 1394 and subscriber circuit for interfaces.

Therefore, according to the present invention, CPU memory remains small, because the present invention does not employ complex protocol such as IP (internet protocol).

CPU also remains small, because 64 Kbps PCM digital

25 conversion means and the conversion hardware from 64 Kbps
 to 98.304, 199.0608, and 393.216 Mbps are employed.

Further, according to the present invention, voice is natural, because ISOCH channel is employed.

Further, according to the present invention, 64 Kbit data

can be transmitted from the extension node by using the conventional 64 Kbit CODE, and the addresses are managed by a simple table by fixing the channel assigned at the time of the call-in and call-out.

- 5 Further, the data are transferred continuously even during the bus reset, by optimizing the buffer.

Further, various voice and image applications on various OSs and protocols are compatible with API (Application Program Interface).

- 10 In conclusion, according to the present invention, all the functions such as automatic identification of terminal functions, master-slave communication, slave to slave communication, and master to slave transfer can be implemented.

15

BRIEF EXPLANATION OF THE DRAWINGS

Figure 1 is a block diagram of the switching system of the present invention.

- 20 Figure 2 is an example of a table for managing a gateway node and extension nodes.

Figure 3 is a block diagram of a hardware of the gateway node.

- 25 Figure 4 is a block diagram of the gateway node connected with ISDN (Integrated Services Digital Network).

Figure 5 is a block diagram of a hardware of the extension node.

Figure 6 is an illustration of signal conversion between voice/ISDN and IEEE1394.

Figure 7 is an illustration of IEEE 1394 packet.

Figure 8 is a block diagram of an extension node which transmits and receives voice signal only.

Figure 9 is a block diagram of the protocol stack for
5 extnsion-extension communication by voice only.

Figure 10 is a block diagram of gateway node connected with PSTN (Public Switched Telephone Network).

Figure 11 is a block diagram of an extension node for voice and visual signal.

10 Figure 12 is a block diagram of residential gateway provided with a telephone gateway and a TV gateway.

Figure 13 is a flow chart of call-in process.

Figure 14 is a flow chart of call-out process.

Figure 15 is a block diagram of a conventional IP
15 (Internet Protocol) telephony.

PREFERRED EMBODIMENT OF THE INVENTION

Modes of embodiment of the present invention are
20 explained, referring to the drawings.

A protocol stack of the exchange system is shown in Figure 1. The exchange system of the present invention comprises gateway node 700 which is connected with a network such as a analogue line and ISDN (Integrated Services Digital
25 Network), one or more extension nodes 201, and IEEE 1391 bus 301.

Extension node 201 which includes a voice node and a non-voice node is connected with the physical layer of bidirectional IEEE 1394 bus 301. Therefore, the number of

extension nodes 201 are smaller than or equal to sixty-three, according to the IEEE 1394 protocol. Further, extension nodes 201 are equal on IEEE 1394 bus 301. Extension node 201 has its own protocol according to its own function.

- 5 Extension node 201 can exchange information data and control data with another extension node 201 which has the identical protocol. Further, extension node 201 can recognize a bus reset due to addition or deletion of terminal, or dissolution of trouble.

- 10 Gateway 700 includes a rate conversion means for converting the outside/extension data transfer rates in order to provide call channels for seamless communication between the outside line and extension line. Further, in response to requests from outside line or extension line, gateway 700
15 grasps network status, and secures network resource, particularly the isochronous (ISOCH) channel as call channel. Furthermore, gateway 700 switches lines for transferring or holding under requests from outside or extension lines.

- The normal or long distance standard in IEEE 1394 are
20 employed for IEEE1394 bus 301.

Communication channels by a various means such as ISDN S-IF, CATV, ADSL (Asymmetric Digital Subscriber Line) and ATM (Asynchronous Transfer Mode) are used for outside line 101 connected with gateway 700.

- 25 Resource manager 401 prepares a control table for controlling extension table 201 and gateway node700. The control table is exemplified in Figure 2. Simplified exchange number as shown in Figure 2 is a number fixed to the physical layer.

IEEE 1394 node control as shown in Figure 2 is executed every node ID (identifier) in such a manner that gateway node 700 and extension node 201 can refer to the simplified exchange number and the node class through IEEE 1394 bus 5 301.

When a bus reset occurs, the node ID is changed, according to the Tree Identify process and the Self Identify process. In this case, resource manager 401 rewrites the control table and notifies each extension node 201 of that change.

10 Node class is classified by its function into voice class, gateway class, and dataless class. A relay, for example, belongs to the dataless class. Further, an automatic recording function during absence in the voice class is indicated by suffix. These classes are identified by a non-
15 shown exchange setup program.

A hardware block diagram of gateway node 700 is shown in Figure 3. IEEE 1394 bus 301 is connected with physical layer device 701 which is further connected through link layer device 702 with both asynchronous (ASYNC) interface 703
20 and isochronous (ISOCH) interface 704. Both ASYNC interface 703 and ISOCH interface 704 are connected through internal bus interface 710 with memory 709 and CPU 708. Gateway node 700 as shown in Figure 3 inputs and outputs outside line signal by using outside line interface
25 such as S-IF to and from memory 709 and CPU 708. B-ch indicated as 706A and ISDN layer 2/layer 3 indicated as 706B are exemplified in Figure 3.

A block diagram of another gateway node 700 connected with ISDN is shown in Figure 4, wherein outside line

interface 705 includes two information channels indicated as B-ch and control channel indicated as D-ch. Buffer 706C as shown in Figure 4 buffers signals as much as two information channels indicated as B-ch.

- 5 Gateway node 700 as shown in Figure 3 or 4 is provided with non-shown exchange setup program.

Concretely, CPU 708 as shown in Figure 3 or 4 accepts setup registration of reception mode and stores it in memory 709 beforehand. The setup registration is sent to CPU 708
10 from extension node 201 through physical layer 701, link layer 702, ASYNC interface 703, and internal interface bus 702. Here, the reception mode is selected by using operation board such as ten key and is stored in memory 709. The reception mode may be, for example, a mode for calling
15 extension node 201 with or without limiting call originators, a mode for recording the voices automatically with or without limiting call originators.

When there is a call-in from ISDN, gateway 700 as shown in Figure 3 or 4 detects the number of the call originator from
20 D-ch through outside line interface 705, and inspects, by using CPU 708, whether the object node is busy, idle, or absent.

When the termination node or the object node is busy, CPU 708 waits for an end of call.

- 25 On the other hand, when the termination node is idle, CPU 708 controls ASYNC interface 703 , secures a bidirectional ISOCH channel, and send the secured channel number to extension node 201. Then, afterward, ISOCH interface 704 is activated under the control by CPU 708, thereby starting

talking through the secured channel.

Further, when the termination node is absent, CPU 708 controls similarly ASYNC interface 703, secures a bidirectional ISOCH channel, and send to extension node 201 the secured channel number, recording ready signal, and recording identifier. Here, the recording identifier may includes a simplified exchange number, time, and serial number, whereby extension node 201 can record automatically the voice through gateway 700 from ISDN.

10 A hardware block diagram of extension node 201 is shown in Figure 5. IEEE 1394 bus 301 is connected through physical layer device 211 and link layer device 212 with both asynchronous (ASYNC) interface 213 and isochronous (ISOCH) interface 214. Both ASYNC interface 213 and ISOCH interface 214 are connected through internal bus interface 220 with memory 221 and CPU 222. Extension node 201 further comprises user terminal 215.

User terminal 215 further comprises user interface 215A including an operation board and voice input/output apparatus such as a microphone and a speaker, and voice memory 215B for automatic recording during absent time. User terminal 215 may comprises a display for receiving visual signals.

The output/input signal from/to user interface 215A is inputted or outputted to/from memory 221 and CPU 222 through CODEC 218, buffer 219, and internal bus interface 220. The output/input signal from/to the operation board is inputted or outputted to/from memory 221 and CPU 222 through terminal controller 216, code extraction unit 217,

and internal bus interface 220. The output/input signal from/to user interface 215B is inputted or outputted similarly.

Extension node 201 transmits and receives the control
5 signal of code extraction unit 217, executes media stream transform of data such as voice data, controls the operation board in user interface 215A, and drives the speaker. The voice data may be coded by CODEC 218 and is sent to buffer 219 every 8 kHz sampling.

10 When the automatic recording at absent time is executed, a header including the recording identifier is received through code extraction unit 217, a media stream of voice data is transformed by CODEC 208. Finally, the voice and the originator number and time stamp in the received header are
15 stored in voice memory 215A.

Next, the communication from an extension node 201 to the other extension node 201 or to the outside line is explained. In this case, CPU 222 inspects, on the basis of call operation by the operation board in user interface 215A, whether the
20 termination node 201 or gateway 700 is busy, idle, or absent.

When the termination node 201 or gateway 700 is idle or absent, CPU 222 send a call request through ASYNC interface 213. In case of extension to extension communication, CPU 222 secures an ISOCH channel for a
25 stream channel immediately after sending the call request, and send the secured channel number to the termination node 201. In case of extension to outside communication, CPU 222 further send the outside line number through gateway 700. Then, CPU 222 sends a call request to the

outside line through gateway 700. Then, CPU 222 secures an ISOCH channel for a stream channel between extension node 201 and gateway 700.

Signal conversion from voice/ISDN signal in the extension
5 node into IEEE1394 signal in the network is illustrated in
Figure 6. Analogue voice signal is sampled at 8 kHz by
CODEC 218, coded by μ -LAW, buffered by buffer 219, and
sent through CPU 222 to IEEE 1394 link layer. Voice signal
is received in the direction reverse to the above-explained
10 procedure. It is desirable that buffer 219 has a capacity
sufficient enough to output the voice signals collectively, even
when IEEE 1394 bus stops and resumes.

IEEE 1394 packet signals and distributions thereof are
illustrated in Figure 7. Time slots of 5 μ sec 801 and 802
15 contains ISOCH channels 811, 821, 812, and 822. For,
example, a first node is assigned to channel 1 of which first
and second time slots are time slots 811 and 812, respectively.
Likewise, a second node is assigned to channel 2 of which
first and second time slots are time slots 821 and 822,
20 respectively. Data allocated to these time slots are converted
into analogue signal by CODEC 208, and outputted from a
speaker of user terminal 215. The voice signal inputted into a
microphone is processed in the direction reverse to the
above-mentioned procedure for the speaker output.

25 In the present invention, synchronous interface may be, for
example, an interface for isochronous (ISOCH) transfer.

A block diagram of an extension node 201 exclusively used
for voice signal is shown in Figure 8.

IEEE 1394 bus 301 is connected with ASYNC interface 703

and ISOCH interface 704 through physical layer device 701 and link layer device 702.

ASYNC interface 703 connected with control/memory unit 730 selects a channel in the network and controls signal
5 timings. Control/memory unit 730 stores network status by using reference means such as a table of physical ID and telephone number. Display unit 720 and operation unit 721 which are connected with control/memory unit 730. Display unit 720 displays network status on the basis of data from
10 control/memory unit, while operation unit 721 accepts telephone number input.

ISOCH interface 704 outputs voice at 100 to 400 MHz every 125 μ sec, at real time, without re-transmitting, even
15 when some errors have occurred. The outputted voice signal is converted into 64 Kbps ISDN signal by rate conversion means 731, processed by μ LAW/CODEC 732, and outputted from speaker 734. Reversely, voice signal inputted into microphone 733 is transferred to μ LAW/CODEC 732.

Further, stream data processing means 723 connected with
20 stream data input means 722 connected with rate conversion means 731 data format of the voice signal and stores it in a non-shown memory.

A protocol stack of extension to extension communication is shown in Figure 9. Here, the extension nodes are used
25 exclusively for voice signal.

Bus managers 750 and 751 as switching equipments are mounted on ASYNC interface 703 /ISOCH interface 704 on link layer 702 on physical layer 701. Bus managers 750 and 751 control voice interface, rate conversion, and call

information

Concretely, bus managers 751 for client and 750 for server control by using a common manner for the client and server microphone/speaker, operation board, 721, and display 721.

- 5 Particularly, CTI 724 (Computer Telephony Integration) of bus manager 750 for server controls connection and operation of terminals such as user terminal 215 as shown in Figure 5, stores the control information, executes notification to all the terminals, and accepts calls/requests from the terminals.
- 10 Here, the control information stored in CTI 724 includes a correspondence table between the physical IDs of IEEE 1394 and actual telephone number of the terminals. CTI 724 resumes communication line instantly, by reading out the correspondence table, when the bus is reset.
- 15 The intermission of communication caused by the bus reset due to Plug and Play is minimized, because CTI 724 always make each terminal rewrite every change in the correspondence table so as to restore the connection merely by notifying the terminal of the change of the physical ID due
- 20 to the Plug and Play.

A block diagram of gateway 700 connected with PSTN (public switched telephone network) is shown in Figure 10. IEEE 1394 interface including bus manager manages connection with IEEE 1394 bus 301 and executes voice

25 processing, while ISDN/analogue outside line interface connects digital voice stream through API (application program interface) of bus manager with S interface of ISDN (S-IF) or the analogue interface.

CPU 708 converts protocols for connecting IEEE1394 bus

301 and S-IF/PSTN 302. Concretely, address conversion between IEEE 1394 bus ID and telephone number, data conversion between high speed data on IEEE 1394 bus 301 and low speed data on PSTN 302.

5 Line manager 752 accepts call-out from the bus manager and call-in from the outside line. Line manager 752 connects the call-in with extension node 201. Conventional hardware/software are employed for lower layers L2 (761) and L3 (762), CODEC 763, and control/memory unit 764.

10 A block diagram of extension node 201 for telephone data and TV data is shown in Figure 11. Operation board 726 controls telephone 725 and TV 731. All the data from operation board 726 is sent to gateway 700 through bus manager and ASYNC channel. For example, billing
15 information for digital TV is sent through ASYNC channel as telephone data.

20 A block diagram of gateway node 700 for telephone data and TV data is shown in Figure 11. Telephone gateway 727 connects NCU (Network Control Unit) with IEEE 1394 bus 301, while TV gateway 728 connects digital TV with IEEE 1394 bus 301. Operational data for controlling terminals and server are sent through ASYNC channel to IEEE 1394 bus 301. For example, the billing information for digital TV is one of the operational data of telephone. Telephone gateway 727
25 and TV gateway 728 are included in CPU 708 as shown in Figure 3.

TV signal stream on IEEE 1394 bus 301 is outputted on non-shown TV display through physical layer, link layer, ASYNC interface, ISOCH interface, and TV-AVF/C (TV .

Audio Vidual signal controller).

TV-AV signal may be MPEG (Moving Picture Expert Group of ISO/IEC) picture, while TV hardware may include STB (set top box).

- 5 A flow chart of the call-in operation is shown in Figure 13. A call-in accepted by S-IF or PSTN interface 761 is received as a connection request at step 901. The call-in from analogue line is detected at ring detection at step 902. Then, at step 903, CPU 708 selects either one of the three modes;
- 10 automatic transfer by ND (number display), global call-in for all the extension nodes, or manual call-in to an object extension node.

- 15 In case of the automatic transfer by ND at step 904, an ISOCH channel is selected on the basis of ND number, prescribed numbers to be transferred, and extension data.

In case of the global call-in at step 906, call signals to all the terminals are sent through ASYNC interface 704.

- 20 In case of the manual transfer at step 908, a call signal is sent to a switching node or prescribed terminal, on the basis of an instruction from operation board 721.

After selecting the mode, CPU 708 decides to connect the call-in with extension node 201, or to reply "busy" to the outside line, depending upon the status signals periodically sent from all the extension nodes 201.

- 25 When CPU 708 confirms a reply from extension node 201, CPU 708 secures ISOCH channel for extension node 201 and ISOCH channel for the outside line at step 914, thereby starting communication at step 915. ISOCH channels are secured till the end of call.

Further, when the call status is changed in extension node 201, the status change is notified simultaneously and directly to all the extension nodes 201 with telephone terminals. Here, the call status is a signal indicating whether a node is busy or
5 idle.

A flow chart of call-out from an extension to the other extension or an outside line is shown in Figure 14. Connection is requested by connection request at step 950 and by inputting an object telephone number or object ID at
10 step 951. The object ID is an object extension number, or an object outside line number together with prescribed number for calling out the outside line. When gateway node 700 accepts the connection request, it confirms the call status at step 952. When the object is idle, ISOCH channel for
15 transmission is secured at step 953, and Ch-ID is secured at step 954. Further, the call status is sent to every node at step 955. Likewise, ISOCH channel for reception is secured at step 956, Ch-ID thereof is secured at step 957, and the call status is sent to every node at step 958. Then, at step 959, the
20 call-out signal is sent to the object through ASYNC channel. When the object replies, communication is started through ISOCH channel. On the other hand, when the object does not reply, call signal is sent repeatedly, and a call status indicating that the object does not reply is sent to the node
25 which requests the cal-out. When the call-out is ended successfully at step 962, or when on-hook by the node which requests the call-out is detected due to at step 965, ISOCH channel is released at step 966, and call status is sent to every node.

As explained above, ISOCH channel is secured every call.

Every call transmits one packet of maximum 16 Bit voice data every cycle within 1 μ sec of ISOCH transfer.

5 The hardware necessary for the exchange system of the present invention includes CODEC for voice signal and rate conversion device together with physical layer device and link layer device.

The API in the present invention feed the high bit rate voice data on IEEE 1394 into the processing unit.

10 The terminals of the present invention store the latest status, because the status change in a terminal is immediately notified to all the terminals. Therefore, the latest status can be confirmed before bus reset and call. Particularly, busy status of the object can be confirmed before
15 the beginning of ISOCH transfer.

20

25

What is claimed is:

1. A network switching system wherein stream data transferred on a serial bus are exchanged through a gateway
5 between an outside line and an extension node, or between an extension node and the other extension node, wherein said extension node comprises:

control/memory unit for storing physical identifiers and telephone numbers of said gateway node and extension nodes
10 and for controlling said network;

an asynchronous interface, for selecting said extension node and controlling a switching timing, connected with said control/memory unit;

a rate conversion unit for converting data rate of said
15 stream data in said network into that in said outside line, or converting the other way around; and

an isochronous interface, for transmitting and receiving said stream data, connected with said rate conversion unit.

2. The network switching system according to Claim 1,
20 wherein said extension node further comprises:

a microphone for inputting said stream data ;

a speaker for outputting said stream data; and

a codec, for encoding and decoding said stream data, connected with said microphone, said speaker and said rate
25 conversion unit for encoding and decoding said stream data.

3. The network switching system according to Claim 1, wherein said extension node further comprises:

a stream data take-in unit, for storing said stream data, connected with said rate conversion unit; and

a stream data processing unit, for processing said stream data, connected with said stream data take-in unit.

4. The network switching system according to Claim 1, wherein said asynchronous interface and said isochronous
5 interface are connected with a bus manager which controls said asynchronous interface, said isochronous interface, said control/memory unit, and said rate conversion unit.

5. A gateway which comprises a first switching unit for controlling extension nodes connected with a serial bus for
10 isochronous transfer, and second switching unit for exchanging stream data between an outside line and said extension nodes, wherein:

said first switching unit comprises a bus manager connected with an asynchronous interface and an
15 isochronous interface; and

said second switching unit comprises a line manager connected with a codec and a control/memory unit,

wherein said line manager exchanges said stream data between said outside line and said extension node, according
20 to a request from said bus manager, and said bus manager manages a call-in to said extension node and a call-out from said extension node.

6. An information terminal which comprises a telephone for transmitting and receiving telephone signal through a
25 serial bus, a TV set for receiving TV signal through said serial bus, and a bus manager for controlling said serial bus, wherein said bus manager comprises two pairs of an asynchronous interface and an isochronous interface for said telephone signal and said TV signal, respectively.

7. A gateway which comprises a telephone gateway and a TV gateway which are connected with a bus manager, wherein:

said telephone gateway transfers telephone signal from
5 public switched telephone network to a serial bus, and transfers the other way around;

said TV gateway receives TV signal from TV line, and transfer said TV signal to said bus manager; and

said bus manager comprises two pairs of an asynchronous
10 interface and a isochronous interface for transferring said telephone signal and said TV signal, respectively.

8. A call-in signal processing method for a network switching system using asynchronous and isochronous transfer modes, wherein stream data transferred on a serial
15 bus are exchanged through a gateway between an outside line and an extension node, or between an extension node and the other extension node, which comprises the steps of:

selecting at said gateway which of an automatic transfer by number display, a global call-in, or a manual call-in on
20 the basis of setup data;

calling one or more extension nodes;

securing one or more isochronous channels on the basis of responses from said extension nodes;

allowing said extension nodes to start talking;

25 sending simultaneously call status of a station of which call status is changed to all the extension node connected with said serial bus.

9. A call-out signal processing method for a network switching system using asynchronous and isochronous

transfer modes, wherein stream data transferred on a serial bus are exchanged through a gateway between an outside line and an extension node, or between an extension node and the other extension node, which comprises the steps of:

5 receiving at said gateway a call-out from said extension node ;

 confirming at said gateway a call status of call object;

 securing an isochronous channel for transmission;

 sending said call status to all the extension nodes;

10 securing an isochronous channel for reception;

 allowing said call object to start talking, when said call object has responded, while sending, to said extension node which carried out call-out, such a call status that indicates that said call object does not respond, when said call object

15 has not responded;

 releasing said isochronous channels for transmission and reception, when detecting an on-hook of said extension node which has made said call-out; and

 sending said call status to all the extension nodes.


20

25

ABSTRACT

To provide a switching system with telephone switching function mainly on the basis of hardware processing by using
5 isochronous channel which is a real time communication channel. The switching system comprises a gateway node connected with ISDN (Integrated Services Digital Network) and PSTN (Public Switched Telephone Network), and one or more extension nodes, and a serial bus such as IEEE 1394
10 bus. The gateway node transforms data rate of outside line into data rate of extension node, and the other way around, and secure a seamless communication channel. Concretely, the gateway node secures an isochronous channel, according to a request from the extension nodes or the outside line, and
15 executes switching such as transfer or reservation. A resource manager holds a table for managing the gateway node and extension node.

FIG. 1



F I G . 2

IEEE 1394 NODE MANAGEMENT	SIMPLIFIED SWITCHING NUMBER	Node CLASS
Node ID 0	EXTENSION #1	EXTENSION Node
Node ID 1	EXTENSION #2	EXTENSION Node
Node ID 2	EXTENSION #3	EXTENSION Node- AUTOMATIC RECORDING
Node ID 3	EXTENSION #4	GATEWAY Node

F I G. 3




FIG. 4





FIG. 5



୧୭୫




FIG. 7






FIG. 8



உ-உ-உ



F I G.10




FIG. 11





FIG. 12



F I G.13




FIG.14





FIG. 15



F-10110

Application for United States Patent

DECLARATION AND POWER OF ATTORNEY

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name;

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

NETWORK SWITCHING SYSTEM WITH ASYNCHRONOUS AND
ISOCRONOUS INTERFACE

the specification of which:
(check one)

☒ (is attached hereto)
_____ was filed on _____
as Application Serial No. _____
and was amended on _____ (if applicable)

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, § 1.56*

I hereby claim foreign priority benefits under Title 35, United States Code, § 119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

Prior Foreign Application(s)			priority claimed	
<u>100198/1999</u>	<u>Japan</u>	<u>07/04/1999</u>	<u>X</u>	
(Number)	(Country)	(Day/Month/Year Filed)	yes	no
_____	_____	_____	yes	no
(Number)	(Country)	(Day/Month/Year Filed)		
_____	_____	_____	yes	no
(Number)	(Country)	(Day/Month/Year Filed)		

I hereby claim the benefit under Title 35, United States Code, § 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, § 112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, § 1.56 which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

_____	_____	_____
(Application Serial No.)	(Filing Date)	(Status: patented, pending, abandoned)

Power of Attorney: As a named inventor, I hereby appoint Sean M. McGinn, Reg. No. 34, 386, and Frederick W. Gibb, III, Reg. No. 37,629, as attorneys and/or agents to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. All correspondence should be directed to McGinn & Gibb, P.C., 1701 Clarendon Boulevard, Suite 100, Arlington, Virginia 22209. Telephone calls should be directed to McGinn & Gibb, P.C. at (703) 294-6699.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full Name of Sole
Joint Inventor, If Any Akira KOYAMA
Inventor's Signature Akira Koyama Date March 24, 2000
Residence Tokyo, Japan
Citizenship Japanese
Post Office Address c/o NEC Corporation, 7-1, Shiba 5-chome, Minato-ku,
Tokyo, Japan

Full Name of Second
Joint Inventor, If Any _____
Inventor's Signature _____ Date _____
Residence _____
Citizenship _____
Post Office Address _____

Full Name of Third
Joint Inventor, If Any _____
Inventor's Signature _____ Date _____
Residence _____
Citizenship _____
Post Office Address _____

Full Name of Fourth
Joint Inventor, If Any _____
Inventor's Signature _____ Date _____
Residence _____
Citizenship _____
Post Office Address _____

(An additional sheet(s) is/are attached hereto if the present invention includes more than four inventors.)

*Title 37, Code of Federal Regulations, § 1.56:

(a) A patent by its very nature is affected with a public interest. The public interest is best served, and the most effective patent examination occurs when, at the time an application is being examined, the Office is aware of and evaluates the teachings of all information material to patentability. Each individual associated with the filing and prosecution of a patent application has a duty of candor and good faith toward the Patent and Trademark Office, which includes a duty to disclose to the Office all information known to that individual to be material to patentability as defined in this section. The duty to disclose information exists with respect to each pending claim until the claim is canceled or withdrawn from consideration, or the application becomes abandoned.

(b) Under this section, information is material to patentability when it is not cumulative to information already of record or being made of record in the application, and (1) it establishes by itself or in combination with other information, a prima facie case of unpatentability; or (2) it refutes, or is inconsistent with, a position the applicant takes in: (i) opposing an argument of unpatentability relied on by the Office, or (ii) asserting an argument of patentability.